

TECHNICAL DATA

Fluke i400s AC Current Clamp



Key features

- Companion to your scope or power quality meter to measure up to 400 A AC
- Only current clamp available with a CAT IV 600 V / CAT III 1000 V safety rating
- Specially designed to offer maximum utility in a compact shape
- Take accurate current readings without breaking the circuit
- Soft non-slippery overmold handle
- Optional PM9081/001 BNC/Banana adapter for DMM's
- Two ranges: 40 A and 400 A, 10 and 1 mV/Amp output
- Max. conductor Ø 32 mm

Product overview: Fluke i400s AC Current Clamp

Fluke current clamps extend the current ranges of digital multimeters, power quality analyzers, and portable oscilloscopes and are available for both AC and AC/DC environments. The Fluke i400s is specially designed to offer maximum utility in a compact shape and is the only current clamp available with a CAT IV 600 V / CAT III 1000 V safety rating.

Specifications: Fluke i400s AC Current Clamp

Specifications



| Nominal current range | 40 A Range | 0.5 A to 40 A |
|---------------------------------|--------------------------------|--------------------------|
| | 400 A Range | 5 A to 400 A |
| Basic accuracy | 40 A Range | 2% + 0.015 A (45-400 Hz) |
| | 400 A Range | 2% + 0.04 A (45-400 Hz) |
| Phase shift | 40 A Range | |
| | 0.5 to 1 A | Unspecified |
| | 1 A to 5 A | 4° |
| | 5 A to 10 A | 3° |
| | 10 A to 20 A | 3° |
| | 20 A to 40 A | 2° |
| | 40 A to 400 A | NA |
| | 400 A Range | |
| | 0.5 to 1 A | NA |
| | 1 A to 5 A | NA |
| | 5 A to 10 A | Unspecified |
| | 10 A to 20 A | 2° |
| | 20 A to 40 A | 2° |
| | 40 A to 400 A | 1.5° |
| Typical bandwidth | 40 A Range | 5 Hz - 10 kHz |
| | 400 A Range | 5 Hz - 10 kHz |
| Output level(s) | 40 A Range | 10 mV/A |
| | 400 A Range | 1 mV/A |
| Crest factor | 40 A Range | ≤ 3 |
| | 400 A Range | ≤ 3 to 300 A |
| | | ≤ 2.5 to 400 A |
| Safety Specifications | | |
| Safety | CAT IV, 600 V, CAT III, 1000 V | |
| Maximum non-destructive current | 1000 V AC | |
| Mechanical and General Sp | pecifications | |
| Warranty | 1 year | |
| Maximum conductor size | 32 mm (1.25 inches) | |
| Output cable length | 2.5 m (8.2 ft) | |
| BNC adapter | Yes | |
| Dimensions | 150 x 70 x 30 mm | |
| Weight | 114 g | |

2 Fluke Corporation Fluke i400s AC Current Clamp



Ordering information



Fluke i400s



Fluke. Keeping your world up and running.®

Fluke Corporation PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853 In Canada (800) 36-FLUKE From other countries +1 (425) 446-5500 www.fluke.com ©2024 Fluke Corporation. Specifications subject to change without notice. 05/2024

Modification of this document is not permitted without written permission from Fluke Corporation.