

# GPIB Bus Isolator/Expander

## NI GPIB-120B

- IEEE 488.1 and IEEE 488.2 compatible
- 60 VDC continuous electrical isolation
- 2,500 VDC noncontinuous overvoltage isolation between GPIB ports and between each port and power supply based on 5 s withstand test
- Transfer rates
  - Up to 1.2 MB/s (buffered mode)
  - Up to 450 kB/s (unbuffered mode)
- Expands the number of GPIB devices allowed on the bus to 28
- Bidirectional expansion – controllers, talkers, and listeners can exist on either side of the expansion
- Software transparent – no software modifications required
- Signal buffering extends the maximum GPIB cable limit to 40 m (device load every 2 m of bus cable)
- External 12 VDC universal power supply (100 to 240 VAC input)
- Meets CE and FCC Class A electromagnetic compatibility (EMC) requirements
- Optional rack-mount or DIN-rail/wall-mount kit



## Overview

The National Instruments GPIB-120B is a GPIB bus isolator and expander. You can use it in test and measurement systems to provide electrical isolation as well as expand the number of devices allowed on the GPIB bus.

The NI GPIB-120B provides an electrically isolated interface to one or more GPIB devices. It offers up to 2,500 VDC of noncontinuous isolation between the GPIB ports and between each GPIB port and the power supply, based on a 5 s dielectric withstand test.

The GPIB-120B also expands the number of devices allowed on the GPIB. The IEEE 488.1 standard prescribes a maximum of 15 electrical device interface loads in a GPIB system. The GPIB-120B increases the number of GPIB system devices from 15 to 28. It also provides bidirectional expansion, where controllers, talkers, and listeners can exist on either side of the expansion.

The GPIB-120B is completely software transparent. You can insert a GPIB-120B into your system without having to rewrite your software application.

## Data Transfer Modes

The GPIB-120B isolator/expander can operate in one of two data transfer modes: unbuffered and buffered. The data transfer mode determines how data is transmitted across the expansion.

In unbuffered mode, each data byte is transmitted using the standard GPIB double-interlocked handshaking protocol, keeping the GPIB-120B isolator/expander transparent.

In buffered mode, the GPIB-120B isolator/expander uses FIFO (first-in-first-out) buffers to buffer data between the remote and local sides of the isolation barrier. For long data streams, the data throughput can be much higher than with unbuffered mode.

The GPIB-120B is capable of data transfers of up to 1.2 MB/s in buffered mode and up to 450 kB/s in unbuffered mode.

## Ordering Information

NI GPIB-120B	
U.S. 120 VAC .....	779651-01
Universal Euro 240 VAC .....	779651-04
U.K. 240 VAC .....	779651-06
Japan 100 VAC .....	779651-07

## BUY NOW!

For complete product specifications, pricing, and accessory information, call (800) 813 3693 (U.S.) or go to [ni.com/gpib](http://ni.com/gpib).

# GPIB Bus Isolator/Expander

## Specifications

### IEEE 488 Compatibility

IEEE 488.1 and IEEE 488.2 compatible

### Maximum IEEE 488 Bus Transfer Rates

Buffered mode ..... Up to 1.2 MB/s  
Unbuffered mode ..... Up to 450 kB/s

### Physical

Dimensions ..... 16.01 by 9.35 by 3.15 cm  
(6.30 by 3.68 by 1.24 in.)  
Weight ..... 245 g (8.64 oz)

### Power Requirements

Input voltage range ..... 12 to 18 VDC  
Current consumption (@ 12 VDC) ..... 500 mA max, 300 mA typical  
Internally fused (nonreplaceable) ..... F 2.2 A 125 V (fast acting)

### 12 VDC power supply (included)

Input voltage/current range ..... 100 to 240 VAC, 0.4A, 47 to 63 Hz

### Isolation, Continuous (operating)

Between GPIB ports ..... 60 VDC  
Between each port and  
power supply ..... 60 VDC

### Isolation, Noncontinuous (overvoltage)

Between GPIB ports ..... 2,500 VDC, verified by a  
dielectric withstand test, 5 s max  
Between each port and  
power supply ..... 2,500 VDC, verified by a  
dielectric withstand test, 5 s max

## Operating Environment

Ambient temperature ..... 0 to 55 °C

*(Note: For the GPIB-120B to operate over the entire specified ambient temperature range, stacking the product is not recommended.)*

Relative humidity ..... 10 to 90%, noncondensing

Maximum altitude ..... 2,000 m  
(at 25 °C ambient temperature)

Pollution degree ..... 2

Indoor use only

*(in accordance with IEC-60068-2-1, IEC-60068-2-2, and IEC-60068-2-56)*

## Storage Environment

Ambient temperature ..... -20 to 70 °C

Relative humidity ..... 5 to 95%, noncondensing

*(in accordance with IEC-60068-2-1, IEC-60068-2-2, and IEC-60068-2-56)*

## Shock and Vibration

Operational shock ..... 30 g peak, half-sine, 11 ms pulse

*(in accordance with IEC-60068-2-27; test profile developed in accordance with MIL-PRF-28800F)*

## Random vibration

Operating ..... 5 to 500 Hz, 0.3 grms

Nonoperating ..... 5 to 500 Hz, 2.4 grms

*(in accordance with IEC-60068-2-64; nonoperating test profile developed in accordance with MIL-PRF-28800F, Class 3)*

## Compliance and Safety

Online at [ni.com/certification](http://ni.com/certification).

# NI Services and Support



NI has the services and support to meet your needs around the globe and through the application life cycle – from planning and development through deployment and ongoing maintenance. We offer services and service levels to meet customer requirements in research, design, validation, and manufacturing. Visit [ni.com/services](http://ni.com/services).

## Training and Certification

NI training is the fastest, most certain route to productivity with our products. NI training can shorten your learning curve, save development time, and reduce maintenance costs over the application life cycle. We schedule instructor-led courses in cities worldwide, or we can hold a course at your facility. We also offer a professional certification program that identifies individuals who have high levels of skill and knowledge on using NI products. Visit [ni.com/training](http://ni.com/training).

## Professional Services

Our Professional Services Team is composed of NI applications engineers, NI Consulting Services, and a worldwide National Instruments Alliance Partner program of more than 600 independent consultants and

integrators. Services range from start-up assistance to turnkey system integration.

Visit [ni.com/alliance](http://ni.com/alliance).



## OEM Support

We offer design-in consulting and product integration assistance if you want to use our products for OEM applications. For information about special pricing and services for OEM customers, visit [ni.com/oem](http://ni.com/oem).

## Local Sales and Technical Support

In offices worldwide, our staff is local to the country, giving you access to engineers who speak your language. NI delivers industry-leading technical support through online knowledge bases, our applications engineers, and access to 14,000 measurement and automation professionals within NI Developer Exchange forums. Find immediate answers to your questions at [ni.com/support](http://ni.com/support).

We also offer service programs that provide automatic upgrades to your application development environment and higher levels of technical support. Visit [ni.com/ssp](http://ni.com/ssp).

## Hardware Services

### NI Factory Installation Services

NI Factory Installation Services (FIS) is the fastest and easiest way to use your PXI or PXI/SCXI combination systems right out of the box. Trained NI technicians install the software and hardware and configure the system to your specifications. NI extends the standard warranty by one year on hardware components (controllers, chassis, modules) purchased with FIS. To use FIS, simply configure your system online with [ni.com/pxiadvisor](http://ni.com/pxiadvisor).

### Calibration Services

NI recognizes the need to maintain properly calibrated devices for high-accuracy measurements. We provide manual calibration procedures, services to recalibrate your products, and automated calibration software specifically designed for use by metrology laboratories. Visit [ni.com/calibration](http://ni.com/calibration).

### Repair and Extended Warranty

NI provides complete repair services for our products. Express repair and advance replacement services are also available. We offer extended warranties to help you meet project life-cycle requirements. Visit [ni.com/services](http://ni.com/services).



[ni.com](http://ni.com) • (800) 813 3693

National Instruments • [info@ni.com](mailto:info@ni.com)

