

Arbitrary Waveform Generators

► AWG400 Series



► AWG420.

The AWG400 Series performs a wide range of modulated (I&Q) and mixed signal simulations (analog and digital) for wireless and wired data communication, in addition to semiconductor device characterization. The AWG400 Series is ideal for design or manufacturing test engineers who need to replicate marginal and erroneous analog and mixed signal conditions. The only product in its class offering 200 MS/s, 16-Bit vertical resolu-

tion, 2 or 3 channel configurations and optional digital outputs (32 or 48). The AWG400 Series is a superior choice for those who need an additional channel, longer memory or higher vertical resolution. The color display, graphical user interface and stand-alone Microsoft Windows-based waveform creating utility (ArbExpress™) supports quick creation, editing and output of custom or imported waveforms.

► Features & Benefits

2 or 3 Independent Waveform Channels

16-Bit Vertical Resolution

200 MS/s Sample Rate

Up to 16 M Point Record Length

Optional 32/48-Bit, 100 MHz (CMOS) Digital Data Generator for Mixed-signal Device Testing

4 or 6 Digital Marker Outputs

Independent Channel Internal Noise Generator

Independent Channel Skew Control

Independent Channel External Signal ADD-INPUT

External Clock and External Reference Inputs

► Applications

Designing, Testing and Deploying:

Quadrature Digitally Modulated I&Q Signals and Displays

Mixed (Analog/Digital) Signals

Stimulus Signals for Imaging Display and Recording Devices (CCD, LCD)

Enhanced/Corrupted Playback of DSO Captured Signals

Simulation Waveform Vectors Imported from Mathcad, Matlab, Excel and others

Network Communications Physical Layer Testing:

ITU-T (E1, E2, E3)

TI.102 (DS1, DS1A, DS1C)

Fibre Channel (FC133E)


SDH/SONET (OC1/STM0, OC3/STM1)

D2


100Base-TX

Arbitrary Waveform Generators

▶ AWG400 Series



▶ $\pi/4$ DQPSK vector diagram.



▶ $\pi/4$ DQPSK with 20% quadrature error.

▶ Characteristics

Modulation Standards and Display Types

Modulation Types –

- ▶ BPSK
- ▶ QPSK
- ▶ OQPSK
- ▶ $\pi/4$ DQPSK
- ▶ 8PSK
- ▶ 16QAM
- ▶ 64QAM
- ▶ 256QAM
- ▶ User defined

Modulation Displays –

- ▶ I(t), Q(t)
- ▶ R(t), $\varphi(t)$
- ▶ Eye Diagram I
- ▶ Eye Diagram Q
- ▶ Vector Diagram
- ▶ Constellation
- ▶ Magnitude Spectrum
- ▶ Phase Spectrum

Arbitrary Waveforms

Waveform Length – 64 to 4,050,000 points (64 to 16,200,000 points with Opt. 01).

Waveform Segment Length – ≥ 64 points, in multiple of 1.

Sequence Steps – One to 8,000 steps (All channels operate the same sequence).

Repeat Counter – One to 65,536 or infinite.

Function Generator Waveforms

Operation Mode – Continuous mode only.

Waveform Shape – Sine, Triangle, Square, Ramp, Pulse or DC.

Frequency – 1.000 Hz to 10.00 MHz.

Amplitude (Standard) –

Range: 0.020 V_{p-p} to 2 V_{p-p} into 50 Ω .
Resolution: 1 mV.

Amplitude (Option 05) –

Range: 0.020 V_{p-p} to 5 V_{p-p} into 50 Ω .
Resolution: 1 mV.

Offset (Standard) –

Range: -1.000 V to +1.000 V into 50 Ω .
Resolution: 1 mV.

Offset (Option 05) –

Range: -2.500 V to +2.500 V into 50 Ω .
Resolution: 1 mV.

DC Level (Standard) –

DC waveform only.
Range: -1.000 V to +1.000 V into 50 Ω .
Resolution: 1 mV.

DC Level (Option 05) –

DC waveform only.
Range: -2.500 V to +2.500 V into 50 Ω .
Resolution: 1 mV.

Phase –

Range: -360° to +360°.

Resolution:

- 1.000 Hz to 20 kHz: 0.036° step.
- 20.01 kHz to 200 kHz: 0.36° step.
- 200.1 kHz to 2.000 MHz: 3.6° step.
- 2.001 MHz to 4.000 MHz: 7.2° step.
- 4.001 MHz to 5.000 MHz: 9° step.
- 5.001 MHz to 8.000 MHz: 14.4° step.
- 8.001 MHz to 10.00 MHz: 18° step.

Polarity – Normal, Invert.

Duty Cycle – Range: 0.1% to 99.9%, Pulse waveform only.

Resolution:

- 1.000 Hz to 200 kHz: 0.1% step.
- 200.1 kHz to 2.000 MHz: 1% step.
- 2.001 MHz to 4.000 MHz: 2% step.
- 4.001 MHz to 5.000 MHz: 2.5% step.
- 5.001 MHz to 8.000 MHz: 4% step.
- 8.001 MHz to 10.00 MHz: 5% step.

Marker Out –

Marker1 Pulse Width:

Hi/Lo: 20%/80% of Period.

Marker2 Pulse Width:

Hi/Lo: 50%/50% of Period, except 5.001 MHz to 8.000 MHz.

Hi/Lo: 52%/48% of Period, at 5.001 MHz to 8.000 MHz.

Marker Level: TTL level.

Clock Generator

Sample Frequency – 10.00000 kS/s to 200.0000 MS/s.

Resolution Accuracy – 7 digits/ ± 2 ppm ($\pm 0.0002\%$).

Period Jitter (rms) – 7 ps at 200 MHz (typical).

Cycle Jitter (rms) – 12 ps at 200 MHz (typical).

Main Analog Output

Number of Outputs – AWG430: 3, AWG420: 2.

Output Style – Complementary (standard), Single-ended (Opt. 05).

Output Connector/Impedance –

BNC front panel (50 Ω).

Vertical Resolution – 16-Bit.

D/A Converter (DNL/INL) –

± 3 LSB at 25 $^{\circ}\text{C}$ / ± 4 LSB at 25 $^{\circ}\text{C}$.

Skew Time Between Channels –

$\leq \pm 100$ ps (Relative to Ch 1).

Variable Delay (Range/Resolution/Accuracy) –

-2.52 ns to +2.52 ns/70 ps / ± 70 ps at 25 $^{\circ}\text{C}$.

Complementary Output

Amplitude/Range – -2.0 V to +2.0 V (into 50 Ω)/20 mV to 2.0 V_{p-p} (into 50 Ω).

Resolution/DC Accuracy –

1 mV/ $\pm 1.5\%$ of setting + 2 mV (Offset = 0 V).

Step Response (10% to 90%) – (-1 and 1

waveform data, 0 V offset, filter "Through").

Rise Time: ≤ 4.0 ns.

Fall Time: ≤ 4.0 ns.

Settling Time: $\pm 3\%$ (after 50 ns from rise/fall edges).

Aberration: $\pm 10\%$ (amplitude > 1.0 V), $\pm 7\%$

(amplitude ≤ 1.0 V).

SFDR – (Signal frequency: 1.0 MHz, amplitude:

1.0 V, offset: 0 V, filter "Through") -74 dB (at 50 MS/s),

-74 dB (at 100 MS/s), -62 dB (at 150 MS/s).

Offset

Range/Resolution –

-1.00 V to +1.00 V (into 50 Ω)/1 mV.

Accuracy – $\pm 1\%$ of offset + 10 mV (amplitude = 20 mV, waveform data 0).

Filter

Type – Bessel low pass filter 1 MHz, 5 MHz, 20 MHz, 50 MHz.

Rise Time (10% to 90%) –

350 ns, 70 ns, 18 ns, 7 ns.

Delay From Trigger –

350 ns, 70 ns, 18 ns, 7 ns (group delay).

Direct Output (Standard)

Range/Amplitude – -0.25 V to +0.25 V (into 50 Ω)/20 mV to 0.5 V (into 50 Ω).

Resolution/DC Accuracy/Offset –

1 mV/ $\pm 1.5\%$ of setting + 2 mV/ ≤ 10 mV.

Step Response (10% to 90%) – (filter "Through").

Rise/Fall Time: ≤ 3.0 ns/ ≤ 3.0 ns.

Single-ended Output (Opt. 05)

Range/Amplitude – -5.0 V to +5.0 V (into 50 Ω)/20 mV to 5.0 V_{p-p} (into 50 Ω).
Resolution/DC Accuracy – 1 mV/ ± (1.5% of amplitude + 2 mV)(Offset = 0 V).
Range / Resolution – -2.500 V to +2.500 V (into 50 Ω)/1 mV.
Accuracy – ± (1% of offset + 10 mV)(amplitude = 20 mV, waveform data 0).
Step Response (10% to 90%) – (-1 and 1 waveform data, 0 V Offset, Filter "Through").
 Rise Time: ≤5.0 ns; Fall Time: ≤5.0 ns.
 Settling Time: ±3% (after 50 ns from rise/fall edges).
 Aberration: ±10% (amplitude >1.0 V), ±7% (amplitude ≤1.0 V).
SFDR – (Signal frequency: 1.0 MHz, amplitude: 1.0 V_{p-p}, offset: 0 V, filter "Through") -72 dB (at 50 MS/s), -70 dB (at 100 MS/s), -60 dB (at 150 MS/s).

Filter

Type – Bessel low pass filter 1 MHz, 5 MHz, 20 MHz, 50 MHz.
Rise Time (10% to 90%) – 350 ns, 70 ns, 18 ns, 7 ns.
Delay From Trigger – 350 ns, 70 ns, 18 ns, 7 ns (Group Delay).

Noise (All channels independent)

Range/Resolution – -130 dBm/Hz to -95 dBm/Hz/1 dBm/Hz.
Accuracy/Type – ±2.5 dB at (-95 dBm/Hz to -130 dBm/Hz at 10 MHz)/Gaussian.
Flatness – ±2.5 dB (1 MHz to 100 MHz at -95 dBm/Hz reference 50 MHz).
Output Connector – Part of analog front panel BNC.

Internal Trigger Generator

Range/Resolution/Accuracy – 1.0 μs to 10.0 s/ 3 digits, minimum 0.1 μs/±0.1%.

Auxiliary Outputs

Marker

Maximum Data Rate – 200 Mb/s.
Number of Outputs – AWG430: 6.
 AWG420: 4 (2 per channel).
Level/Impedance – Hi: ≥2.4 V, Lo: ≤0.1 V (into 50 Ω) 74LVC54A output driver/50 Ω.
Rise/Fall Time (10% to 90%) – 4 ns maximum.
Output Skew – ≤±100 ps.
Output Connector – BNC rear panel.

Master Clock Out

Level/Impedance – 1 V_{p-p} (into 50 Ω) ±0.3 V/50 Ω.
Frequency/Output Connector – 100 MHz to 200 MHz/BNC rear panel.

Digital Data (Output from P4116, Opt. 03).

Number of Outputs – Ch 1 = 16, Ch 1+2 = 32, Ch 1+2+3 = 48. Each channel D0-D15 = 16 Bits + clock.
Output Connector – Each channel 34-Pin (header pin connector), P4116 CMOS Pod.
Maximum Data Rate – 10 kb/s to 100 Mb/s.
Level/Impedance – Hi: ≥2.3 V, Lo: ≤0.1 V (into 50 Ω) 74LVC541A output driver/50 Ω.
Rise Time (10% to 90%) – 3 ns Maximum.
Skew Time – 1 ns (typical) (between clock signals and data).
Data Invalid Time – 4 ns.

10 MHz Reference

Amplitude / Impedance – 1 V_{p-p} min (into 50 Ω), 3 V_{p-p} max (into 1 MΩ) / Impedance: 50 Ω AC coupled.
Output Connector – BNC rear panel.

Display Monitor

Format/Connector – VGA/D-sub 9-Pin, rear panel.

Auxiliary External Input

Trigger In

Impedance/Polarity – 1 kΩ or 50 Ω/positive or negative.
Input Voltage Range/Threshold – 1 kΩ ±10 V or 50 Ω ±5 V/-5.0 V to 5.0 V.
Accuracy/Resolution – ± (5% of setting level + 0.1 V)/0.1 V.
Minimum Pulse Width/Dead Time – 10 ns (0.2 V Amplitude)/≤65 clock + 200 ns maximum.
Delay to Analog Out – 50 ns + 1 clock.
Connector – BNC rear panel.

Event In

Number of Events In/Input Signal – 4-Bits/4 event bits + strobe.
Threshold/Pulse Width – TTL level/≥100 ns.
Maximum Input Level/Impedance – 0 V to +5 V (DC + peak AC)/2.2 kΩ, pulled-up to +5 V.
Delay to Analog Out – ≤130 Clock + 400 ns.
Connector – 9-Pin D-sub rear panel.

ADD In

Number of ADD In – Ch1, Ch 2, Ch 3 Independent.
Input Range/Impedance – -1 V to 1 V (DC + peak AC)/50 Ω.
Band Width (-3 dB)/Amplitude Accuracy – ≥50 MHz at 1 V_{p-p} input/±5%.
Connector – BNC rear panel.

10 MHz Reference In

Input Range/Impedance – 0.2 V_{p-p} to 3 V_{p-p}, maximum ±10 V/50 Ω, AC coupled.
Frequency Range/Connector – 10 MHz ±0.1 MHz/BNC rear panel.

Master Clock In

Sensitive Voltage/Threshold – ≥0.4 V_{p-p}/0.5 Vdc.
Minimum Pulse Width/Maximum Input Voltage – 2 ns/± 2 VDC.
Frequency Range/Impedance – DC to 200 MHz/50 Ω.
Connector – BNC rear panel.

Environment/Other

Operation Mode – Continuous, Triggered, Gated, Enhanced.
Display – Color TFT LCD.
Display Area/Resolution – Horizontal: 13.06 cm (5.14 in.), Vertical: 9.70 cm (3.81 in.)/640x480.

Data Storage

Internal Hard Disk – 10.0 GB.
Flash Disk (Option 10) – 128 MB.
Floppy Disk – 3.5", 1.44 MB.

Environment

Temperature – Operating/Nonoperating: +10 °C to +40 °C/-20 °C to +60 °C.
Humidity – Operating/Nonoperating: 20% to 80%/5% to 90%.
Altitude – Operating/Nonoperating: Up to 3,000 m (10,000 ft.)/up to 12,000 m (40,000 ft.).
Vibration – Operating / Nonoperating: 0.27 G_{RMS}, 5 Hz to 500 Hz/2.28 G_{RMS}, 5 Hz to 500 Hz.
Shock – Nonoperating: 294 m/s² (30 G), half-sine, 11 ms duration (three time each axis).
EMC – EC Council Directive 89/336/EEC (EC-92), AD/NZS 2064.1/2.
Safety – UL 3111-1, CSA C22.2 No. 1010.1, EN61010-1, IEC61010-1.

Power Supply

Rating/Range – 100 to 240 VAC/90 to 250 VAC.
Maximum Power and Current/Frequency – 380 VA/48 to 63 Hz.

Physical Characteristics

AWG420

| Dimensions | mm | in. |
|---------------|-----------|------------|
| Height | 193 | 7.6 |
| Width | 433 | 17.05 |
| Depth | 508 | 20 |
| Weight | kg | lb. |
| Net 14.1 | 31.1 | |

AWG430

| Dimensions | mm | in. |
|----------------|-----------|------------|
| Height | 193 | 7.6 |
| Width | 433 | 17.05 |
| Depth | 508 | 20 |
| Weight | kg | lb. |
| Net 14.4 | 31.7 | |
| With Packaging | 22.3 | 49.12 |

Interfaces – GPIB, Ethernet: 10/100Base-T, RJ-45.
PC Keyboard – 6-Pin mini-DIN, serial communication port.

Arbitrary Waveform Generators

► AWG400 Series

► Ordering Information

AWG420

200 MS/s, 16-Bit, Two-channel Arbitrary Waveform Generator.

AWG430

200 MS/s, 16-Bit, Three-channel Arbitrary Waveform Generator.

All Include: User/Programmer manual 070-A809-00, GPIB programming examples 062-A258-00, sample waveform library disk 062-A257-00, performance verification 062-A270-00, Cal. Certificate no charge, AXW100 ArbExpress™ Software Utility CD (063-3763-00), power cord.

Please specify power plug when ordering.

Recommended Accessories

Service Manual – Order 070-A811-00.

Protective Cover – Order 200-3696-01.

ArbExpress™ – PC-based stand-alone waveform creation utility.

Options

Opt. 01 – 16 M point waveform memory.

Opt. 03 – CMOS Digital Data Outputs – 32/48-Bit (number of digital output bits depends on AWG400 model).

Opt. 05 – Single-ended output (alternative for standard complementary output).

Opt. 10 – 128 MB Flash disk and standby switch (alternative for standard hard disk drive).

Note: Option 10 is for ATE and system usage needing 24x7 hour operation. Also adds capability to power on/off by rear panel main switch.

Opt. 1R – Rackmount.

Power Plug Options

Opt. A0 – North America Power.

Opt. A1 – Universal EURO Power.

Opt. A2 – United Kingdom Power.

Opt. A3 – Australia Power.

Opt. A5 – Switzerland Power.

Opt. A99 – No Power Cord or AC Adapter.

Opt. AC – China Power.

Service

Opt. C3 – Calibration Service 3 Years.

Opt. C5 – Calibration Service 5 Years.

Opt. D1 – Calibration Data Report.

Opt. D3 – Calibration Data Report 3 Years (with Opt. C3).

Opt. D5 – Calibration Data Report 5 Years (with Opt. C5).

Opt. R3 – Repair Service 3 Years.

Opt. R5 – Repair Service 5 Years.

Warranty

One year parts and labor.

Contact Tektronix:

ASEAN / Australasia / Pakistan (65) 6356 3900

Austria +43 2236 8092 262

Belgium +32 (2) 715 89 70

Brazil & South America 55 (11) 3741-8360

Canada 1 (800) 661-5625

Central Europe & Greece +43 2236 8092 301

Denmark +45 44 850 700

Finland +358 (9) 4783 400

France & North Africa +33 (0) 1 69 86 80 34

Germany +49 (221) 94 77 400

Hong Kong (852) 2585-6688

India (91) 80-22275577

Italy +39 (02) 25086 1

Japan 81 (3) 6714-3010

Mexico, Central America & Caribbean 52 (55) 56666-333

The Netherlands +31 (0) 23 569 5555

Norway +47 22 07 07 00

People's Republic of China 86 (10) 6235 1230

Poland +48 (0) 22 521 53 40

Republic of Korea 82 (2) 528-5299

Russia, CIS & The Baltics +358 (9) 4783 400

South Africa +27 11 254 8360

Spain (+34) 901 988 054

Sweden +46 8 477 6503/4

Taiwan 886 (2) 2722-9622

United Kingdom & Eire +44 (0) 1344 392400

USA 1 (800) 426-2200

USA (Export Sales) 1 (503) 627-1916

For other areas contact Tektronix, Inc. at: 1 (503) 627-7111

Last Update March 01, 2004

Our most up-to-date product information is available at:
www.tektronix.com

Product Area Assessed: The planning, design/
development and manufacture of electronic
Test and Measurement instruments.



Copyright © 2004, Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.

08/04 HB/WWW

76W-14841-4

Tektronix
Enabling Innovation